Distribution Category:
Mathematics and
Computer Science (UC-405)

ARGONNE NATIONAL LABORATORY
9700 South Cass Avenue
Argonne, IL 60439

ANL-92/47

A Test Implementation of the MPI Draft Message-Passing Standard

by

William Gropp and Ewing Lusk

Mathematics and Computer Science Division

December 1992

This work was supported in part by the Office of Scientific Computing, U.S. Department of Energy, under Contract W-31-109-Eng-38.

Contents

1 Introduction **1**

1.1 Structure of the Send and Receive Library 1
1.2 C and Fortran 2
1.3 Additions 2
1.4 Omissions 3
1.5 Restrictions 3

2 Comments on the Draft Standard **3**

3 Starting and Stopping Processes **4**

4 Very Simple User Interface **4**

5 Examples **4**

6 Availability **5**

7 Basic Routines for Point-to-Point Messages **5**

7.1 General Communication Control 6
7.2 Contiguous Communications 8
7.2.1 General Routines 8
7.2.2 Blocking Routines 13
7.2.3 Nonblocking Routines 18
7.3 Constant Stride Communications 22
7.3.1 General Routines 22
7.3.2 Blocking Routines 27
7.3.3 Nonblocking Routines 32
7.4 General Scatter/Gather 37
7.4.1 General Routines 37
7.4.2 Blocking Routines 42
7.4.3 Nonblocking Routines 46
7.5 Process Groups 50
7.6 Communication Contexts 57
7.7 Program Management 58
7.8 Utility Routines 59

A Test Implementation of the MPI Draft Message-Passing Standard

by

William Gropp and Ewing Lusk

Abstract

Message passing is a common method for programming parallel computers. The lack of a standard has significantly impeded the development of portable software and libraries for these machines. Recently, an ad-hoc committee was formed to develop a standard for message-passing software for parallel computers. This group first met in April 1992 at a workshop sponsored in part by the Center for Research on Parallel Computation (CRPC). Four of the attendees at that meeting produced a draft standard, henceforth referred to as the MPI (Message-Passing Interface) draft standard. After review by a larger group, and significant changes in the document, a meeting was held in November to discuss the MPI draft standard. This document is a result of those discussions; it describes a running implementation of most of the proposed standard, plus additional routines that were suggested by the discussions at the November meeting.

1 Introduction

This document describes a test implementation of the Message-Passing Interface (MPI) draft standard. Supplying an implementation along with the standard itself provides several benefits. It allows the draft standard to be tested for expressivity and implementability. It brings to light potential inconsistencies and omissions in the draft standard as the draft standard develops. It allows experiments that measure possible restrictions on performance imposed by the draft standard.

Subject to the small number of restrictions and omissions cited below, it is an implementation of all of the draft standard. It also includes other routines that might be considered for inclusion in the draft standard as it develops.

1.1 Structure of the Send and Receive Library

This implementation provides a relatively large number of simple operations that are small and therefore easy to describe precisely. Larger operations can then be implemented and defined in terms of these operations. The basic send and receive operations are broken down as follows:

$$\left[\begin{array}{c} c \\ s \\ g \end{array}\right]\left[\begin{array}{c} n \\ b \\ s \end{array}\right]\left[\begin{array}{c} send \\ recv \end{array}\right]\left[\begin{array}{c} \sqcup \\ h \end{array}\right]\left[\begin{array}{c} \sqcup \\ rr \end{array}\right],$$

where the first letter specifies the layout of the data, the second specifies the extent to which the calling process synchronizes with the local message-passing subsystem and with the remote one, the next four letters specify a send or receive operation, and the final letter(s) specify optional additional functionality.

- Data layout

  c (contiguous) The bytes are to be sent from or received into a contiguous region of memory, described by starting address and length.

  s (stride) The data to be sent consists of data items of the same type and size, separated by a constant distance (stride) in memory, described by a starting address, length of a single item, and number of items.

g (gather) The data to be sent consists of data items of varying lengths and addresses, described by an array of addresses and lengths.

- Synchronization

  n (nonblocking) The operation returns control to the user immediately, to facilitate overlapping computation and communication.

  b (blocking) the operation does not return until the message area is available for reuse.

  s (synchronous) The operation does not return until the message has been received by the destination process (in the case of a send) or the acknowledgment has been sent (in the case of a receive).

- Send or Receive

  send (send) Transfer a message from the calling process to the specified one.

  recv (receive) Transfer a message into memory if specified conditions are met.

- Heterogeneity

  ␣ (default) This is the default.

  h (heterogeneous) The message will be processed in such a way that differing data representations on different machines will be taken into account. On the [c] and [s] routines this requires a data type parameter. On the [g] operations, it requires data type information in the vector describing the data location.

- Alternate Protocol

  ␣ (default) This is the default.

  rr (receiver ready) The operation will take advantage of any underlying protocol that is available when the receiver of a message is known to have issued the receive before the corresponding send is executed.

The routines specified in the current draft standard, which use a mode argument to specify the synchronization level, can easily be defined (and implemented) in terms of these operations, and we have done so. This organization makes it easy to experiment with and understand capabilities not currently in the draft, such as the `rr` and `h` options.

1.2 C and Fortran

The implementation described here is for the C language. Enough of the Fortran versions of these routines have been provided to write and run a simple program. These are the routines `MPI_csend`, `MPI_crecv`, a few inquiry routines (e.g., `MPI_getid`), and `MPI_main`.

1.3 Additions

In order to write actual programs, it was necessary to add a few routines for program management. We have added the routines `MPI_main` and `MPI_stopall` for this purpose.

We also have suggested a small set of routines (see Section 4) that are at a higher level than the draft standard, in order to meet the needs of users who wish to express a message-passing algorithm, but who do not need to know about the more complex performance issues this implementation and the draft standard itself tries to address, such as overlapping communication and computation with `n` or reducing latency with `rr`.

We also added an error value for "unknown mode."

1.4 Omissions

We have not implemented the time and date routines since there seemed to be a consensus that they need not be part of this standard. We can add them if they are desired. We did not implement the `MPI_pack`, etc., routines because they now seem to be subsumed by the [s] and [g] versions of send and receive. The man pages do not yet include the "Description" section; this can in most cases be taken from the draft standard.

1.5 Restrictions

This is a very preliminary, fast implementation, designed to allow experimentation with at least some of the ideas in the draft standard. In the interest of getting it out very quickly, we have taken some shortcuts. We intend to remove these as time goes by. Currently (November 25, 1992) the following restrictions apply to the implementation of the draft standard:

- There is only one process group. Since the draft standard does not specify that there be more than one, this implementation is (draft) standard-conforming. However, it is not currently possible to run a program that uses more than one group. (You are likely to get the "too many groups" error.)
- There is only one communication context. Again, this conforms to the letter but not the spirit of the draft standard.
- Neither selection on source nor selection on type range (that is, the negative type values) is implemented. This restriction allows us to use existing (vendor-supplied) message-passing implementations on a variety of machines.

2 Comments on the Draft Standard

One reason for doing a prototype implementation is to identify potential problems with the specification of the standard. In this section, we detail some of the problems that we have detected.

- The routines that take mode for "blocking," "nonblocking," or "synchronous" return a value whose meaning depends on the value of mode.
- The routines to get information on "the last message" are tricky to specify precisely, because the notion of "the last message" is imprecise. In particular, "the last message" means the last message received, probed, or otherwise looked at. This means that an `MPI_probe` will change the values that these routines will return. It is also unclear how process groups and communications contexts affect the meaning of "the last message."
- The standard specifies a 32 bit type field. With 64 bit systems on the horizon, this seems shortsighted.
- Because there are no minimum number of communications contexts or process groups specified, an implementation can conform to the standard by providing a single communication context and a single process group. This is in fact what our implementation does.
- Were process groups to be implemented, the interpretation of the destination field (`dest`) and the return value from `MPI_infos` is unclear. Is it the process id? Is it the rank of the process in the current group? What is the meaning of receive-from-any-processor as a selection in a receive routine?
- There is no way for the user to control the ranking of processes in a process group.

- There is no way to discover the length of a message before receiving it into a user buffer. This prohibits using dynamic memory allocation (either by `malloc` in C or by explicit allocation of work areas in Fortran 77) to manage messages that are of unknown length at compile time.
- As the examples demonstrate, there is no attractive way to determine such simple things as the process id or the number of processes.
- Error handling is unattractive. As written, the user must check return codes. While we agree that users (particularly software library writers) need this option, not all users will be diligent about checking the return codes. One of the examples below emphasizes this.

3 Starting and Stopping Processes

In this section we give the specifications for routines needed to support the creation and destruction of the processes that will be communicating. We have added a routine `MPI_stopall` that causes all processes in an application to exit.

It has been our experience that a major source of portability problems is in how a parallel program is started up and initializes its environment. We have added `MPI_main` as a standardized way to accomplish this. This replaces `main` in C and `PROGRAM` in Fortran 77. In addition, it may be useful to provide a subroutine-level interface for initializing the MPI package.

4 Very Simple User Interface

A very simple interface can be defined that consists of the routines

```
MPI_numpids  =  MPI_infog( 0, 0, 0 )
MPI_mypid    =  MPI_getid(0)
MPI_send     =  MPI_cbsend
MPI_recv     =  MPI_cbrecv
```

as well as `MPI_main` for defining a program.

5 Examples

We present here two programs that send a message around a ring of processors. The Fortran version of this program is

```
      integer function MPI_main()
      integer buf, size, type, np, right, left
      integer actlen
c
      size  = 4
      type  = 3
      np    = MPI_infog( 0, 0, 0 )
      right = mod( MPI_getid(0) + 1, np )
      left  = mod( MPI_getid(0) - 1 + np, np )

      if (MPI_getid(0) .eq. 0) then
        buf    = 1
        actlen = MPI_csend( 'blocking', buf, right, type, size )
        actlen = MPI_crecv( 'blocking', buf, left,  type, size )
      else
```

```
        actlen = MPI_crecv( 'blocking', buf, left, type, size )
        actlen = MPI_csend( 'blocking', buf, right, type, size )
      endif
      MPI_main = 0
      return
      end
```

The C version of this program is

```
#include "../include/mpi.h"

int MPI_main( argc, argv )
int  argc;
char **argv;
{
    int buf, siz = sizeof(int), type = 3, np, right, left;

    np    = MPI_infog( 0, 0, (int *)0 );  /* Number of processes */
    right = (MPI_getid(0) + 1) % np;
    left  = (MPI_getid(0) - 1 + np) % np;

    if (MPI_getid(0) == 0) {
        buf = 1;
        MPI_csend( "blocking", &buf, right, type, siz );
        MPI_crecv( "blocking", &buf, left,  type, siz );
        }
    else {
        MPI_crecv( "blocking", &buf, left, type, siz );
        MPI_csend( "blocking", &buf, right, type, siz );
        }
    return 0;
}
```

6 Availability

This implementation is available by anonymous ftp from `info.mcs.anl.gov`. In the directory `pub/mpi` the file `mpi.man.ps.Z` is this document. The file `mpi.tar.Z` contains a compressed tar file of this implementation. The implementation is built on top of the Chameleon system; the file `chameleon.tar.Z` is all that is needed to build Chameleon for a variety of parallel computers (including groups of workstations). To use MPI on a system of workstations, either `p4` or `pvm` are needed. Both are available from netlib (`netlib@ornl.gov`); we have included a recent version of `p4` in the file `p4-1.2.tar.Z` in the `/pub/mpi` directory for convenience.

7 Basic Routines for Point-to-Point Messages

In this section we describe the routines that form the lowest level of the implementation. They are designed to be consistent with the upper-level routines.

7.1 General Communication Control

MPI_cancel **MPI_cancel**

MPI_cancel — Cancel a previously initiated nonblocking send or receive

Input Parameter

msgid Message id returned by a call to a nonblocking send or receive

Synopsis

```
int MPI_cancel( msgid )
int msgid;
```

Location

```
mpi.c
```

MPI_infos **MPI_infos**

MPI_infos — Determine the source process of a pending receive

Synopsis

```
int MPI_infos()
```

Returns

The source of the just received message.

Location

```
mpi.h
```

MPI_infot **MPI_infot**

MPI_infot — Determine the type of the last receive

Synopsis

```
int MPI_infot()
```

Returns

The source of the just received message.

Location

`mpi.h`

MPI_probe **MPI_probe**

MPI_probe — Check for pending messages

Input Parameters

source	the PID of the process sending the message
type	the message type

Returns

Length of pending message if available, else -1.

Synopsis

```
int MPI_probe( source, type )
int source, type;
```

Location

`mpi.c`

MPI_stats **MPI_stats**

MPI_stats — Check the status of a nonblocking send or receive

Input Parameter

msg_id	Message id returned by a call to a nonblocking send or receive

Returns

Length of available message if it is pending, else -1.

Synopsis

```
int MPI_stats( msg_id )
int msg_id;
```

Location

mpi.c

MPI_wait **MPI_wait**

MPI_wait — Block until a nonblocking send or receive operation has completed

Input Parameter

msg_id id returned by a nonblocking send or receive routine (of any type)

Returns

Number of bytes sent or received, or -1 on error.

Synopsis

```
int MPI_wait( msg_id )
int msg_id;
```

Location

mpi.c

7.2 Contiguous Communications

7.2.1 General Routines

MPI_crecv **MPI_crecv**

MPI_crecv — Draft standard contiguous receive

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_crecv( mode, buf, source, type, maxlen )
char *mode;
void *buf;
int  source, type, maxlen;
```

Location

```
mpic.c
```

MPI_crecvh — Friendly contiguous heterogeneous receive

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message
datatype	type of data

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_crecvh( mode, buf, source, type, maxlen,datatype )
char *mode;
void *buf;
int  source, type, maxlen,datatype;
```

Location

```
mpic.c
```

MPI_crecvhrr — Friendly contiguous heterogeneous receive for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message
datatype	type of data

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_crecvhrr( mode, buf, source, type, maxlen, datatype )
char *mode;
void *buf;
int  source, type, maxlen, datatype;
```

Location

```
mpic.c
```

MPI_crecvrr — Friendly contiguous receive for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_crecvrr( mode, buf, source, type, maxlen )
char *mode;
void *buf;
int  source, type, maxlen;
```

Location

mpic.c

MPI_csend **MPI_csend**

MPI_csend — Draft standard contiguous send

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to send
dest	destination processor
type	message type
len	length in bytes of message

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_csend( mode, buf, dest, type, len )
char *mode;
void *buf;
int  dest, type, len;
```

Location

mpic.c

MPI_csendh **MPI_csendh**

MPI_csendh — Friendly contiguous heterogeneous send

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to send
dest	destination processor
type	message type
len	length in bytes of message
datatype	type of data

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_csendh( mode, buf, dest, type, len, datatype )
char *mode;
void *buf;
int  dest, type, len, datatype;
```

Location

mpic.c

MPI_csendhrr — Friendly contiguous heterogeneous send for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to send
dest	destination processor
type	message type
len	length in bytes of message
datatype	type of data

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_csendhrr( mode, buf, dest, type, len, datatype )
char *mode;
void *buf;
int  dest, type, len, datatype;
```

Location

mpic.c

MPI_csendrr — Friendly contiguous send for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to send
dest	destination processor
type	message type
len	length in bytes of message

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_csendrr( mode, buf, dest, type, len )
char *mode;
void *buf;
int  dest, type, len;
```

Location

```
mpic.c
```

7.2.2 Blocking Routines

MPI_cbrecv — Blocking contiguous receive

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message

Returns

Number of bytes actually received.

Synopsis

```
int MPI_cbrecv( buf, source, type, maxlen )
void *buf;
int  source, type, maxlen;
```

Location

```
mpic.c
```

MPI_cbrecvh **MPI_cbrecvh**

MPI_cbrecvh — Blocking contiguous heterogeneous receive

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message
datatype	type of data

Returns

Number of bytes actually received.

Synopsis

```
int MPI_cbrecvh( buf, source, type, maxlen, datatype )
void *buf;
int  source, type, maxlen, datatype;
```

Location

```
mpic.c
```

MPI_cbrecvhrr **MPI_cbrecvhrr**

MPI_cbrecvhrr — Blocking contiguous heterogeneous receive for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message
datatype	type of data

Returns

Number of bytes actually received.

Synopsis

```
int MPI_cbrecvhrr( buf, source, type, maxlen, datatype )
void *buf;
int  source, type, maxlen, datatype;
```

Location

```
mpic.c
```

MPI_cbrecvrr — Blocking contiguous receive for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message

Returns

Number of bytes actually received.

Synopsis

```
int MPI_cbrecvrr( buf, source, type, maxlen )
void *buf;
int  source, type, maxlen;
```

Location

```
mpic.c
```

MPI_cbsend — Blocking contiguous send

Input Parameters

buf	buffer to send
dest	destination

type	message type
len	length in bytes of message

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_cbsend( buf, dest, type, len )
void *buf;
int  dest, type, len;
```

Location

```
mpic.c
```

MPI_cbsendh — Blocking contiguous heterogeneous send

Input Parameters

buf	buffer to send
dest	destination
type	message type
len	length in bytes of message
datatype	type of data

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_cbsendh( buf, dest, type, len, datatype )
void *buf;
int  dest, type, len, datatype;
```

Location

```
mpic.c
```

MPI_cbsendhrr — Blocking contiguous heterogeneous send for ready receivers

Input Parameters

buf	buffer to send
dest	destination
type	message type
len	length in bytes of message
datatype	type of data

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_cbsendhrr( buf, dest, type, len, datatype )
void *buf;
int  dest, type, len, datatype;
```

Location

```
mpic.c
```

MPI_cbsendrr — Blocking contiguous send for ready receivers

Input Parameters

buf	buffer to send
dest	destination
type	message type
len	length in bytes of message

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_cbsendrr( buf, dest, type, len )
void *buf;
int  dest, type, len;
```

Location

```
mpic.c
```

7.2.3 Nonblocking Routines

MPI_cnrecv **MPI_cnrecv**

MPI_cnrecv — Nonblocking contiguous receive

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_cnrecv( buf, source, type, maxlen )
void *buf;
int  source, type, maxlen;
```

Location

```
mpic.c
```

MPI_cnrecvh **MPI_cnrecvh**

MPI_cnrecvh — Nonblocking contiguous heterogeneous receive

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message
datatype	type of data

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_cnrecvh( buf, source, type, maxlen, datatype )
void *buf;
int  source, type, maxlen, datatype;
```

Location

mpic.c

MPI_cnrecvhrr **MPI_cnrecvhrr**

MPI_cnrecvhrr — Nonblocking contiguous heterogeneous receive for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message
datatype	type of data

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_cnrecvhrr( buf, source, type, maxlen, datatype )
void *buf;
int  source, type, maxlen, datatype;
```

Location

mpic.c

MPI_cnrecvrr **MPI_cnrecvrr**

MPI_cnrecvrr — Nonblocking contiguous receive for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
maxlen	maximum length in bytes of message

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_cnrecvrr( buf, source, type, maxlen )
void *buf;
int  source, type, maxlen;
```

Location

```
mpic.c
```

MPI_cnsend **MPI_cnsend**

MPI_cnsend — Nonblocking contiguous send

Input Parameters

buf	buffer to send
dest	destination
type	message type
len	length in bytes of message

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_cnsend( buf, dest, type, len )
void *buf;
int  dest, type, len;
```

Location

```
mpic.c
```

MPI_cnsendh **MPI_cnsendh**

MPI_cnsendh — Nonblocking contiguous heterogeneous send

Input Parameters

buf	buffer to send
dest	destination
type	message type
len	length in bytes of message
datatype	type of data

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_cnsendh( buf, dest, type, len, datatype )
void *buf;
int  dest, type, len, datatype;
```

Location

```
mpic.c
```

MPI_cnsendhrr **MPI_cnsendhrr**

MPI_cnsendhrr — Nonblocking contiguous heterogeneous send for ready receivers

Input Parameters

buf	buffer to send
dest	destination
type	message type
len	length in bytes of message
datatype	type of data

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_cnsendhrr( buf, dest, type, len, datatype )
void *buf;
int  dest, type, len, datatype;
```

Location

```
mpic.c
```

MPI_cnsendrr **MPI_cnsendrr**

MPI_cnsendrr — Nonblocking contiguous send for ready receivers

Input Parameters

buf	buffer to receive into

source	sending processor
type	message type
maxlen	maximum length in bytes of message

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_cnsendrr( buf, dest, type, len )
void *buf;
int  dest, type, len;
```

Location

```
mpic.c
```

7.3 Constant Stride Communications

7.3.1 General Routines

MPI_srecv **MPI_srecv**

MPI_srecv — Draft standard receive into buffer with constant stride

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_srecv( mode, buf, source, type, lenblk,stride,nblks )
char *mode;
void *buf;
int  source, type, lenblk,stride,nblks;
```

Location

mpis.c

MPI_srecvh **MPI_srecvh**

MPI_srecvh — Friendly heterogeneous receive into buffer with constant stride

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks
datatype	type of data

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_srecvh( mode, buf, source, type, lenblk,stride,nblks,datatype )
char *mode;
void *buf;
int  source, type, lenblk,stride,nblks,datatype;
```

Location

mpis.c

MPI_srecvhrr **MPI_srecvhrr**

MPI_srecvhrr — Friendly heterogeneous receive into a buffer with constant stride for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block

nblks	maximum number of data blocks
datatype	type of data

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_srecvhrr( mode, buf, source, type, lenblk,stride,nblks, datatype )
char *mode;
void *buf;
int  source, type, lenblk,stride,nblks, datatype;
```

Location

```
mpis.c
```

MPI_srecvrr **MPI_srecvrr**

MPI_srecvrr — Friendly receive into buffer with constant stride for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_srecvrr( mode, buf, source, type, lenblk,stride,nblks )
char *mode;
void *buf;
int  source, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```

MPI_ssend — Draft standard send with constant stride

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to send
dest	destination processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_ssend( mode, buf, dest, type, lenblk,stride,nblks )
char *mode;
void *buf;
int  dest, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```


MPI_ssendh — Friendly heterogeneous send with constant stride

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to send
dest	destination processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks
datatype	type of data

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_ssendh( mode, buf, dest, type, lenblk,stride,nblks, datatype )
char *mode;
void *buf;
int  dest, type, lenblk,stride,nblks, datatype;
```

Location

```
mpis.c
```

MPI_ssendhrr — Friendly heterogeneous send with constant stride for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to send
dest	destination processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks
datatype	type of data

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_ssendhrr( mode, buf, dest, type, lenblk,stride,nblks, datatype )
char *mode;
void *buf;
int  dest, type, lenblk,stride,nblks, datatype;
```

Location

```
mpis.c
```

MPI_ssendrr — Friendly send with constant stride for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
buf	buffer to send
dest	destination processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_ssendrr( mode, buf, dest, type, lenblk,stride,nblks )
char *mode;
void *buf;
int  dest, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```

7.3.2 Blocking Routines

MPI_sbrecv — Blocking receive into buffer with constant stride

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks

Returns

Number of bytes actually received.

Synopsis

```
int MPI_sbrecv( buf, source, type, lenblk,stride,nblks )
void *buf;
int  source, type, lenblk,stride,nblks;
```

Location

mpis.c

MPI_sbrecvh — Blocking heterogeneous receive into buffer with constant stride

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks
datatype	type of data

Returns

Number of bytes actually received.

Synopsis

```
int MPI_sbrecvh( buf, source, type, lenblk,stride,nblks, datatype )
void *buf;
int  source, type, lenblk,stride,nblks, datatype;
```

Location

mpis.c

MPI_sbrecvhrr — Blocking heterogeneous receive into buffer with constant stride for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks
datatype	type of data

Returns

Number of bytes actually received.

Synopsis

```
int MPI_sbrecvhrr( buf, source, type, lenblk,stride,nblks, datatype )
void *buf;
int  source, type, lenblk,stride,nblks, datatype;
```

Location

```
mpis.c
```

MPI_sbrecvrr — Blocking receive into buffer with constant stride for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks

Returns

Number of bytes actually received.

Synopsis

```
int MPI_sbrecvrr( buf, source, type, lenblk,stride,nblks )
void *buf;
int  source, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```

MPI_sbsend — Blocking send with constant stride

Input Parameters

buf	buffer to send
dest	destination
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_sbsend( buf, dest, type, lenblk,stride,nblks )
void *buf;
int  dest, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```


MPI_sbsendh — Blocking heterogeneous send with constant stride

Input Parameters

buf	buffer to send
dest	destination
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks
datatype	type of data

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_sbsendh( buf, dest, type, lenblk,stride,nblks, datatype )
void *buf;
int  dest, type, lenblk,stride,nblks, datatype;
```

Location

mpis.c

MPI_sbsendhrr **MPI_sbsendhrr**

MPI_sbsendhrr — Blocking heterogeneous send with constant stride for ready receivers

Input Parameters

buf	buffer to send
dest	destination
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks
datatype	type of data

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_sbsendhrr( buf, dest, type, lenblk,stride,nblks, datatype )
void *buf;
int  dest, type, lenblk,stride,nblks, datatype;
```

Location

mpis.c

MPI_sbsendrr **MPI_sbsendrr**

MPI_sbsendrr — Blocking send with constant stride for ready receivers

Input Parameters

buf	buffer to send
dest	destination
type	message type
lenblk	size in bytes of each data block

stride	number of bytes between the start of each data block
nblks	number of data blocks

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_sbsendrr( buf, dest, type, lenblk,stride,nblks )
void *buf;
int  dest, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```

7.3.3 Nonblocking Routines

MPI_snrecv **MPI_snrecv**

MPI_snrecv — Nonblocking receive into buffer with constant stride

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_snrecv( buf, source, type, lenblk,stride,nblks )
void *buf;
int  source, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```

MPI_snrecvh — Nonblocking heterogeneous receive into buffer with constant stride

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks
datatype	type of data

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_snrecvh( buf, source, type, lenblk,stride,nblks, datatype )
void *buf;
int  source, type, lenblk,stride,nblks, datatype;
```

Location

```
mpis.c
```


MPI_snrecvhrr — Nonblocking heterogeneous receive into buffer with constant stride for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks
datatype	type of data

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_snrecvhrr( buf, source, type, lenblk,stride,nblks, datatype )
void *buf;
int  source, type, lenblk,stride,nblks, datatype;
```

Location

```
mpis.c
```

MPI_snrecvrr **MPI_snrecvrr**

MPI_snrecvrr — Nonblocking receive into buffer with constant stride for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	maximum number of data blocks

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_snrecvrr( buf, source, type, lenblk,stride,nblks )
void *buf;
int  source, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```

MPI_snsend **MPI_snsend**

MPI_snsend — Nonblocking send with constant stride

Input Parameters

buf	buffer to send
dest	destination
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block

nblks number of data blocks

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_snsend( buf, dest, type, lenblk,stride,nblks )
void *buf;
int  dest, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```

MPI_snsendh **MPI_snsendh**

MPI_snsendh — Nonblocking heterogeneous send with constant stride

Input Parameters

buf	buffer to send
dest	destination
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks
datatype	type of data

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_snsendh( buf, dest, type, lenblk,stride,nblks, datatype )
void *buf;
int  dest, type, lenblk,stride,nblks, datatype;
```

Location

```
mpis.c
```

MPI_snsendhrr **MPI_snsendhrr**

MPI_snsendhrr — Nonblocking heterogeneous send with constant stride for ready receivers

Input Parameters

buf	buffer to send
dest	destination
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks
datatype	type of data

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_snsendhrr( buf, dest, type, lenblk,stride,nblks, datatype )
void *buf;
int  dest, type, lenblk,stride,nblks, datatype;
```

Location

```
mpis.c
```

MPI_snsendrr — Nonblocking send with constant stride for ready receivers

Input Parameters

buf	buffer to receive into
source	sending processor
type	message type
lenblk	size in bytes of each data block
stride	number of bytes between the start of each data block
nblks	number of data blocks

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_snsendrr( buf, dest, type, lenblk,stride,nblks )
void *buf;
int  dest, type, lenblk,stride,nblks;
```

Location

```
mpis.c
```

7.4 General Scatter/Gather

These routines use structures named `MPI_DATAVEC` and `MPI_HDATAVEC` (for heterogeneous communication). The definitions of these are in `mpi.h`. `MPI_DATAVEC` is the same as `struct iovec`; this is a structure that contains a pointer to data and the size of that data in bytes. `MPI_HDATAVEC` adds a value that is the type of the data, in `MPI` format.

7.4.1 General Routines

MPI_grecv **MPI_grecv**

MPI_grecv — Draft standard receive into buffer with arbitrary scatter

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_grecv( mode, source, type, desc, bcnt )
char        *mode;
int         source, type, bcnt;
MPI_DATAVEC *desc;
```

Location

`mpig.c`

MPI_grecvh **MPI_grecvh**

MPI_grecvh — Friendly heterogeneous receive into buffer with arbitrary scatter

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format

bcnt number of blocks

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_grecvh( mode, source, type, desc, bcnt )
char         *mode;
int          source, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_grecvhrr **MPI_grecvhrr**

MPI_grecvhrr — Friendly heterogeneous receive into a buffer with arbitrary scatter for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_grecvhrr( mode, source, type, desc, bcnt )
char         *mode;
int          source, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_grecvrr — Friendly receive into buffer with arbitrary scatter for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

If the mode is "nonblocking," returns the integer id of receive to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_grecvrr( mode, source, type, desc, bcnt )
char        *mode;
int         source, type, bcnt;
MPI_DATAVEC *desc;
```

Location

mpig.c

MPI_gsend — Draft standard send with arbitrary gather

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
dest	destination processor
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_gsend( mode, dest, type, desc, bcnt )
char        *mode;
int         dest, type, bcnt;
MPI_DATAVEC *desc;
```

Location

mpig.c

MPI_gsendh — Friendly heterogeneous send with arbitrary gather

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
dest	destination processor
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_gsendh( mode, dest, type, desc, bcnt )
char         *mode;
int          dest, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gsendhrr — Friendly heterogeneous send with arbitrary scatter for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
dest	destination processor

type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_gsendhrr( mode, dest, type, desc, bcnt )
char         *mode;
int          dest, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gsendrr — Friendly send with arbitrary gather for ready receivers

Input Parameters

mode	one of "blocking," "nonblocking," or "synchronous"
dest	destination processor
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

If the mode is "nonblocking," returns the integer id of send to be used in MPI_wait, etc., or -1 on error.

Otherwise, returns the actual length of the message in bytes, or -1 on error.

Synopsis

```
int MPI_gsendrr( mode, dest, type, desc, bcnt )
char        *mode;
int         dest, type, bcnt;
MPI_DATAVEC *desc;
```

Location

mpig.c

7.4.2 Blocking Routines

MPI_gbrecv **MPI_gbrecv**

MPI_gbrecv — Blocking receive into buffer with arbitrary scatter

Input Parameters

source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Number of bytes actually received.

Synopsis

```
int MPI_gbrecv( source, type, desc, bcnt )
int         source, type, bcnt;
MPI_DATAVEC *desc;
```

Location

```
mpig.c
```

MPI_gbrecvh **MPI_gbrecvh**

MPI_gbrecvh — Blocking heterogeneous receive into buffer with arbitrary scatter

Input Parameters

source	sending processor
type	message type
desc	description of data to be scattered, in MPI_HDATAVEC format
bcnt	number of blocks

Returns

Number of bytes actually received.

Synopsis

```
int MPI_gbrecvh( source, type, desc, bcnt )
int          source, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gbrecvhrr **MPI_gbrecvhrr**

MPI_gbrecvhrr — Blocking heterogeneous receive into buffer with arbitrary scatter for ready receivers

Input Parameters

source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Number of bytes actually received.

Synopsis

```
int MPI_gbrecvhrr( source, type, desc, bcnt )
int          source, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gbrecvrr **MPI_gbrecvrr**

MPI_gbrecvrr — Blocking receive into buffer with arbitrary scatter for ready receivers

Input Parameters

source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Number of bytes actually received.

Synopsis

```
int MPI_gbrecvrr( source, type, desc, bcnt )
int         source, type, bcnt;
MPI_DATAVEC *desc;
```

Location

```
mpig.c
```

MPI_gbsend **MPI_gbsend**

MPI_gbsend — Blocking send with arbitrary gather

Input Parameters

dest	destination
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_gbsend( dest, type, desc, bcnt )
int         dest, type, bcnt;
MPI_DATAVEC *desc;
```

Location

```
mpig.c
```

MPI_gbsendh **MPI_gbsendh**

MPI_gbsendh — Blocking send with arbitrary gather

Input Parameters

dest	destination
type	message type
lenblk	size in bytes of each data block
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_gbsendh( dest, type, desc, bcnt )
int          dest, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gbsendhrr **MPI_gbsendhrr**

MPI_gbsendhrr — Blocking heterogeneous send with arbitrary gather for ready receivers

Input Parameters

dest	destination
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_gbsendhrr( dest, type, desc, bcnt )
int          dest, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gbsendrr **MPI_gbsendrr**

MPI_gbsendrr — Blocking send with arbitrary gather for ready receivers

Input Parameters

dest	destination
type	message type

desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Number of bytes sent, or -1 for an error.

Synopsis

```
int MPI_gbsendrr( dest, type, desc, bcnt )
int         dest, type, bcnt;
MPI_DATAVEC *desc;
```

Location

mpig.c

7.4.3 Nonblocking Routines

MPI_gnrecv **MPI_gnrecv**

MPI_gnrecv — Nonblocking receive into buffer with arbitrary scatter

Input Parameters

source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_gnrecv( source, type, desc, bcnt )
int         source, type, bcnt;
MPI_DATAVEC *desc;
```

Location

mpig.c

MPI_gnrecvh **MPI_gnrecvh**

MPI_gnrecvh — Nonblocking heterogeneous receive into buffer with arbitrary scatter

Input Parameters

source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_gnrecvh( source, type, desc, bcnt )
int          source, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gnrecvhrr — Nonblocking heterogeneous receive into buffer with arbitrary scatter for ready receivers

Input Parameters

source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_gnrecvhrr( source, type, desc, bcnt )
int          source, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gnrecvrr — Nonblocking receive into buffer with arbitrary scatter for ready receivers

Input Parameters

source	sending processor
type	message type
desc	description of data to be scattered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Integer id of receive to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_gnrecvrr( source, type, desc, bcnt )
int         source, type, bcnt;
MPI_DATAVEC *desc;
```

Location

mpig.c

MPI_gnsend — Nonblocking send with arbitrary gather

Input Parameters

dest	destination
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_gnsend( dest, type, desc, bcnt )
int         dest, type, bcnt;
MPI_DATAVEC *desc;
```

Location

mpig.c

MPI_gnsendh **MPI_gnsendh**

MPI_gnsendh — Nonblocking heterogeneous send with arbitrary gather

Input Parameters

dest	destination
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_gnsendh( dest, type, desc, bcnt )
int          dest, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gnsendhrr **MPI_gnsendhrr**

MPI_gnsendhrr — Nonblocking heterogeneous send with arbitrary gather for ready receivers

Input Parameters

dest	destination
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_gnsendhrr( dest, type, desc, bcnt )
int          dest, type, bcnt;
MPI_HDATAVEC *desc;
```

Location

mpig.c

MPI_gnsendrr **MPI_gnsendrr**

MPI_gnsendrr — Nonblocking send with arbitrary gather for ready receivers

Input Parameters

source	sending processor
type	message type
desc	description of data to be gathered, in MPI_DATAVEC format
bcnt	number of blocks

Returns

Integer id of send to be used in MPI_wait, etc., or -1 on error.

Synopsis

```
int MPI_gnsendrr( dest, type, desc, bcnt )
int         dest, type, bcnt;
MPI_DATAVEC *desc;
```

Location

mpig.c

7.5 Process Groups

MPI_child **MPI_child**

MPI_child — Get information about the children of a specified group

Input Parameters

gid	process group id
maxlis	size of clist

Output Parameter

clist array containing process group id

Returns

Number of children in the group, or -1 on error.

Synopsis

```
int MPI_child( gid, maxlis, clist )
int gid, maxlis, *clist;
```

Location

group.c

MPI_copyg **MPI_copyg**

MPI_copyg — Create a root group from an existing group

Input Parameter

gid process group id

Returns

The gid of the new root group, or -1 on error.

Synopsis

```
int MPI_copyg( gid )
int gid;
```

Location

group.c

MPI_defrg **MPI_defrg**

MPI_defrg — Define a root group

Input Parameters

nprocs number of processes in the group
plist array of PID that are members of the group

Returns

The gid of the new root group, or -1 on error.

Synopsis

```
int MPI_defrg( nprocs, plist )
int nprocs, *plist;
```

Location

group.c

MPI_freed **MPI_freed**

MPI_freed — Discard the descendants of a specified group

Input Parameter

gid group id

Returns

0 on success, or -1 on error.

Synopsis

```
int MPI_freed( gid )
int gid;
```

Location

group.c

MPI_freeg **MPI_freeg**

MPI_freeg — Discard a specified group and all of its descendents

Input Parameter

gid group id

Returns

0 on success, or -1 on error.

Synopsis

```
int MPI_freeg( gid )
int gid;
```

Location

```
group.c
```

MPI_getid **MPI_getid**

MPI_getid — Determine the group context PID of the calling process for a specified group id number.

Input Parameter

gid	group id

Synopsis

```
int MPI_getid( gid )
int gid;
```

Returns

Relative process number of the calling process in the specified group.

Location

```
mpi.h
```

MPI_infog **MPI_infog**

MPI_infog — Determine the number of processes in a group and return the PID numbers of the group members

Input Parameters

gid	group id
maxlis	size of plist
plist	integer array to hold the members of the group

Returns

The number of members in the group, or -1 on error.

Synopsis

```
int MPI_infog(gid,maxlis,plist)
int gid, maxlis, *plist;
```

Location

```
mpi.c
```

MPI_parent **MPI_parent**

MPI_parent — Determine the group id number of the parent of a specified group

Input Parameter

gid group whose parent is to be found

Returns

The group id of the parent, or -1 on error.

Synopsis

```
int MPI_parent( gid )
int gid;
```

Location

```
group.c
```

MPI_partg **MPI_partg**

MPI_partg — Partition a group into subgroups

Input Parameters

gid group to be partitioned
key key whose value determines the partitioning

Returns

The gid of the subgroup to which the calling process belongs, otherwise -1.

Synopsis

```
int MPI_partg( gid, key )
int gid, key;
```

Location

group.c

MPI_popg **MPI_popg**

MPI_popg — Reestablish the process group context

Returns

The process group id that is reestablished as the root, otherwise -1.

Synopsis

```
int MPI_popg()
```

Location

group.c

MPI_pushg **MPI_pushg**

MPI_pushg — Establish the process group context

Input Parameter

gid The group context to establish

Returns

The number of processes in the group gid, or -1 on error.

Synopsis

```
int MPI_pushg( gid )
int gid;
```

Location

group.c

MPI_rootg **MPI_rootg**

MPI_rootg — Get information about root groups

Input Parameter

maxlis size of rlist

Output Parameter

rlist array of the process group id numbers

Returns

Number of defined root groups, or -1 on error.

Synopsis

```
int MPI_rootg( maxlis, rlist )
int maxlis, *rlist;
```

Location

group.c

MPI_siblg **MPI_siblg**

MPI_siblg — Get information about the siblings of a group

Input Parameters

gid process group id
maxlis size of slist

Output Parameter

slist array of the process group ids

Returns

Number of siblings, or -1 on error.

Synopsis

```
int MPI_siblg( gid, maxlis, slist )
int gid, maxlis, slist;
```

Location

group.c

7.6 Communication Contexts

MPI_infoc — Get information about valid communication contexts

Input parameter

maxlis maximum size of ilist

Output parameter

ilist array containing communication context ID numbers

Synopsis

```
int MPI_infoc( maxlis, ilist )
int maxlis, *ilist;
```

Location

`mpi.c`

MPI_newc — Create a new communication context

Returns

The id number of a new communication context, or -1 on error.

Synopsis

```
int MPI_newc()
```

Location

`mpi.c`

MPI_popc — Reestablish former communication context

Returns

The id number of a new communication context, or -1 on error.

Synopsis

```
int MPI_popc()
```

Location

```
mpi.c
```

MPI_pushc **MPI_pushc**

MPI_pushc — Establish a new communication context

Input Parameter

ccid the ID number of communication context to establish

Returns

0 on success or -1 on error.

Synopsis

```
int MPI_pushc( ccid )
int ccid;
```

Location

```
mpi.c
```

7.7 Program Management

MPI_main **MPI_main**

MPI_main — Name of main program for MPI applications

Note

Use "MPI_main" instead of "main" in C programs, and instead of "PROGRAM <name>" in Fortran programs.

Synopsis

```
(C)
int MPI_main( argc, argv )
int argc;
char **argv;
```

Synopsis

```
(Fortran)
integer function MPI_main()
```

Location

```
mpi.c
```

MPI_stopall **MPI_stopall**

MPI_stopall — stop all processes

Input Parameter

rc return code to pass back to calling environment

Synopsis

```
void MPI_stopall( rc )
```

Location

```
mpi.c
```

7.8 Utility Routines

MPI_error **MPI_error**

MPI_error — Determine the error status

Returns

Integer giving the error status for the preceding call to an MPI routine.

Synopsis

```
int MPI_error()
```

Location

```
mpi.c
```

MPI_etext — Return the text corresponding to an error value

Input Parameter

ierrno Value returned by MPI_error

Synopsis

```
char *MPI_etext( ierrno )
int ierrno;
```

Location

mpi.c

MPI_machine — Get machine name, version, and related information

Returns

A character string giving the name, etc., of the machine.

Synopsis

```
char *MPI_machine( )
```

Location

mpi.c

MPI_infonm — Get information on the machine configuration

Input Parameter

maxlis the size of ilist

Output Parameter

ilist integer array containing information about the system.

ilist[0] - number of physical processors in the machine
ilist[1] - total number of processors in the machine

Synopsis

```
int MPI_infonm( maxlis, ilist )
int maxlis, *ilist;
```

Location

mpi.c

MPI_sync **MPI_sync**

MPI_sync — Synchronize all processes

Synopsis

```
int sync
```

Location

mpi.h

Index

MPI_cancel, 6
MPI_cbrecv, 13
MPI_cbrecvh, 14
MPI_cbrecvhrr, 14
MPI_cbrecvrr, 15
MPI_cbsend, 15
MPI_cbsendh, 16
MPI_cbsendhrr, 16
MPI_cbsendrr, 17
MPI_child, 50
MPI_cnrecv, 18
MPI_cnrecvh, 18
MPI_cnrecvhrr, 19
MPI_cnrecvrr, 19
MPI_cnsend, 20
MPI_cnsendh, 20
MPI_cnsendhrr, 21
MPI_cnsendrr, 21
MPI_copyg, 51
MPI_crecv, 8
MPI_crecvh, 9
MPI_crecvhrr, 9
MPI_crecvrr, 10
MPI_csend, 11
MPI_csendh, 11
MPI_csendhrr, 12
MPI_csendrr, 13
MPI_defrg, 51
MPI_error, 59
MPI_etext, 60
MPI_freed, 52
MPI_freeg, 52
MPI_gbrecv, 42
MPI_gbrecvh, 42
MPI_gbrecvhrr, 43
MPI_gbrecvrr, 43
MPI_gbsend, 44
MPI_gbsendh, 44
MPI_gbsendhrr, 45
MPI_gbsendrr, 45
MPI_getid, 53
MPI_gnrecv, 46
MPI_gnrecvh, 46
MPI_gnrecvhrr, 47
MPI_gnrecvrr, 48
MPI_gnsend, 48
MPI_gnsendh, 49
MPI_gnsendhrr, 49
MPI_gnsendrr, 50
MPI_grecv, 37
MPI_grecvh, 37
MPI_grecvhrr, 38
MPI_grecvrr, 39
MPI_gsend, 39
MPI_gsendh, 40
MPI_gsendhrr, 40
MPI_gsendrr, 41
MPI_infoc, 57
MPI_infog, 53
MPI_infonm, 60
MPI_infos, 6
MPI_infot, 6
MPI_machine, 60
MPI_main, 58
MPI_newc, 57
MPI_parent, 54
MPI_partg, 54
MPI_popc, 57
MPI_popg, 55
MPI_probe, 7
MPI_pushc, 58
MPI_pushg, 55
MPI_rootg, 55
MPI_sbrecv, 27
MPI_sbrecvh, 28
MPI_sbrecvhrr, 28
MPI_sbrecvrr, 29
MPI_sbsend, 30
MPI_sbsendh, 30
MPI_sbsendhrr, 31
MPI_sbsendrr, 31
MPI_siblg, 56
MPI_snrecv, 32
MPI_snrecvh, 33
MPI_snrecvhrr, 33
MPI_snrecvrr, 34
MPI_snsend, 34
MPI_snsendh, 35
MPI_snsendhrr, 35
MPI_snsendrr, 36
MPI_srecv, 22
MPI_srecvh, 23
MPI_srecvhrr, 23
MPI_srecvrr, 24
MPI_ssend, 25
MPI_ssendh, 25
MPI_ssendhrr, 26
MPI_ssendrr, 27
MPI_stats, 7
MPI_stopall, 59
MPI_sync, 61
MPI_wait, 8